

AXIS P5534-E PTZ Dome Network Camera

Outdoor-ready HDTV camera with 18x zoom.



- > HDTV 720p, day/night and H.264
- > Outdoor-ready: IP66 and NEMA 4X rated
- > 18x optical zoom
- > Advanced Gatekeeper functionality
- > High Power over Ethernet (IEEE 802.3at)

The outdoor-ready AXIS P5534-E PTZ Dome Network Camera offers outstanding HDTV-quality video and 18x zoom, enabling surveillance of a large area and great details when zooming in. With quick and reliable installation features, it is ideal for city and perimeter surveillance, and for use at airports and train stations.

AXIS P5534-E provides HDTV 720p in compliance with SMPTE 296M standard of 1280 x 720 pixel resolution, full frame rate, HDTV color fidelity and a 16:9 format. The day and night camera can deliver multiple H.264 and Motion JPEG streams simultaneously.

The PTZ dome camera provides 18x optical and 12x digital zoom with autofocus. With the unique Auto-flip functionality, it can pan 360° to continuously follow an object. The camera's Advanced Gatekeeper functionality enables it to automatically move to a preset position when motion is detected in a pre-defined area.

The IP66- and NEMA 4X-rated AXIS P5534-E provides cost-efficient installation since no external housing is required. It can operate in temperatures from -20 °C (-4 °F) up to 50 °C (122 °F).

AXIS P5534-E is powered with High Power over Ethernet, which makes installation easy since only one cable is needed for carrying power, video and PTZ commands. A High PoE midspan is supplied.

The camera supports local storage with its built-in SD/SDHC memory card slot.



Note: Mounting brackets are sold separately




Technical specifications – AXIS P5534-E PTZ Dome Network Camera

Camera		System integration	
Models	AXIS P5534-E 60 Hz; AXIS P5534-E 50 Hz	Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform from Axis Communications; specifications available at www.axis.com Includes the ONVIF specification available at www.onvif.org Support for AXIS Video Hosting System (AVHS) with One-Click Camera Connection
Image sensor	1/3" progressive scan CCD 1.3 megapixel	Intelligent video	Video motion detection, Advanced Gatekeeper Support for AXIS Camera Application Platform enabling installation of additional applications
Lens	f=4.7 – 84.6 mm, F1.6 – 2.8, autofocus, automatic day/night Horizontal angle of view: 55.2° – 3.2°	Alarm triggers	Video motion detection, AXIS Camera Application Platform, PTZ position, temperature, memory card full
Minimum illumination	Color: 0.74 lux at 30 IRE F1.6 B/W: 0.04 lux at 30 IRE F1.6	Alarm events	File upload via FTP, HTTP and email Notification via email, HTTP and TCP External output, PTZ position, local storage
Shutter time	1/10000 s to 1/4 s	Video buffer	96 MB pre- and post-alarm
Pan/tilt/zoom	E-flip, Auto-flip, 100 preset positions Pan: 360° (with Auto-flip), 0.2° – 300°/s Tilt: 180°, 0.2° – 300°/s 18x optical zoom and 12x digital zoom, total 216x zoom	General	
Pan/tilt/zoom functionalities	Limited guard tour Control queue On-screen directional indicator	Casing	IP66- and NEMA 4X-rated metal casing (aluminum), acrylic (PMMA) clear dome, sunshield (PC/ASA)
Video		Processors and memory	ARTPEC-3, 256 MB RAM, 128 MB Flash
Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG	Power	High Power over Ethernet (High PoE) IEEE 802.3at, max. 30 W AXIS T8123 High PoE Midspan 1-port included: 100-240 V AC, max. 37 W
Resolutions	HDTV 720p 1280x720 to 320x180	Connectors	RJ-45 for 10BASE-T/100BASE-TX PoE IP66-rated RJ-45 connector kit included
Frame rate	H.264: Up to 30/25 fps (60/50 Hz) in all resolutions Motion JPEG: Up to 30/25 fps (60/50 Hz) in all resolutions	Local storage	SD/SDHC memory card slot (card is not included)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F)
Image settings	Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, backlight compensation, fine tuning of behavior at low light, rotation, text and image overlay, privacy mask, image freeze on PTZ	Approvals	EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22, EN 60950-1, KCC Class B IEC 60529 IP66, NEMA 250 Type 4X IEC 60721-4-3 Class 4K1, 4C3, 4M3 EN/IEC 60068-2 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR
Network		Weight	2.0 kg (4.4 lb.)
Security	Password protection, IP address filtering, HTTPS encryption*, IEEE 802.1X network access control*, digest authentication, user access log	Included accessories	AXIS T8123 High PoE Midspan 1-port, IP66-rated RJ-45 connector kit, clear and smoked dome cover, Installation Guide, CD with User's Manual, recording software, installation and management tools, Windows decoder 1-user license
Supported protocols	IPv4/v6, HTTP, HTTPS*, SSL/TLS*, QoS Layer 3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS		

* This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org)

More information is available at www.axis.com

Dimensions



Optional accessories

AXIS T91A Mounting Accessories



AXIS T90A Illuminators



AXIS P8221 Network I/O Audio Module



AXIS T8310 Video Surveillance Control Board



AXIS Camera Station and video management software from Axis' Application Development Partners. For more information, see www.axis.com/products/video/software/