

# **UHI-SBG-0 Series Indoor Housing**



- ► Economical indoor housing with mount
- ► Aluminum mount included
- ► Feed-through wiring option
- ► Glass fiber reinforced ABS
- Accommodates 1/4-inch, 1/3-inch, and 1/2-inch CCD cameras

The UHI-SBG-0 Housing is smartly styled for indoor use. This housing meets customers' demands for attractive housings that are both cost competitive and easy to install. They fit a wide range of 1/4 in., 1/3 in., and 1/2 in. format CCD cameras and varifocal lenses.


#### **Functions**

The design of these housings is unique. Removal of two tamper-resistant screws is all that is necessary to open the cover and totally expose the camera and lens. This allows access to all camera and lens controls when the camera is in its mounted position. Power and video cabling can be routed through liquid tight fittings in the bottom or rear of the housing. To complete this set, a sturdy aluminum feed-through mount is added.

### **Certifications and Approvals**

Product Safety CE, UL, cUL

## **Installation/Configuration Notes**



## Parts Included

Quantity	Component
1	Indoor housing
1	Aluminum bracket

## **Technical Specifications**

#### **Electrical**

Maximum Camera Power Max. 10 W

24 VAC-230 VAC, 50/60 Hz, 0.5 A

Mechanical

Max Camera/Lens Size  $80 \times 60 \times 210 \, mm$ (3.1 x 2.3 x 8.2 in.)  $(W \times H \times L)$ 

Two liquid tight rear fittings accept cable di-Cable Entry

ameters from 6.5 mm to 10.5 mm (0.26 in. to 0.42 in.). Two bottom feed-through liquid tight fittings accept cable diameters from 4.0 mm to 7.0 mm (0.16 in. to 0.28 in.).

3 mm (0.12 in.) thick glass. Window

**Housing Mounting** Includes one J-mount. Four (4) available 1/4 -20 tapped holes.

Removable camera bracket. Mounted with

Camera Mounting one screw.

Construction/Finish Reinforced with glass fiber ABS, stainless

steel hardware.

Finish Dark mushroom. Dimensions See UHI-SBG-0 drawing.

Weight 1.0 kg (2.2 lb) including bracket.

**Environmental** 

Temperature -10°C (14°F) to 50°C (122°F)

**Enclosure Protection** IP30 (indoor use only)

# **Ordering Information**

**UHI-SBG-0 Series Indoor Housing UHI-SBG-0** 

For camera/lens lengths up to 210 mm (8.2 in.)

#### **Accessories**

# **HAC-TAMP01 Tamper Switch**

**HAC-TAMP01** 

Tamper switch kit for HSG and UHI/UHO series enclosures

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Bosch Security Systems B.V. P.O. Box 80002 F.O. BOX 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

11 Bishan Street 21 Singapore 573943 Phone: +65 6258 5511 Fax: +65 6571 2698 apr.securitysystems@bosch.com www.boschsecurity.com