



290A Outdoor housing for Axis Network Cameras

*Camera protection you can rely upon...
...come rain, shine or grime!*

If you're looking to install Axis network cameras outdoors, you'll need to provide them with the right protection.

IP66 classified housings from Axis offer a convenient, durable and tailor-made solution for mounting Axis network cameras outdoors and within other harsh environments.

Made with a solid extruded aluminum casing, outdoor camera enclosures from Axis provide robust protection for tamper-proofing your cameras, and shields them against dust and heavy rain. They even incorporate a temperature controlled heating system that ensures continued camera operation in cold weather conditions.



Take your surveillance outdoors with tailor-made outdoor enclosures for Axis network cameras.

- Tailor-made enclosure solution for the AXIS 2120 and AXIS 2420 Network Cameras
- Weather protected from -20°C to +42°C
- Weatherproof to IP66
- Supplied with integral tamper-proof mounting bracket

290A Outdoor housing for Axis Network Cameras

General

- Outdoor temperature controlled camera housing in extruded aluminum
- Integral tamper proof wall bracket
- Weatherproof to IP66
- Tailor-made for the AXIS 2120 and AXIS 2420
- Comes complete with sunshield, internal power supply and mounting fixings

Installation

- This product shall only be installed by a licensed electrician

Internal Power Supply

- Input voltage: 100 – 240 VAC (50HZ/60HZ)
- Input current: 0.55A at 100 VAC / 0.28A at 240VAC
- Minimum power requirement: 68VA
- Output voltage: 12VDC
- Output current: 1A

Dimensions and Weight

- Internal dimensions (H x W x L):
93 x 130 x 300 mm
(3.66 x 5.12 x 11.81 Inches)
- External dimensions (H x W x L):
410 x 180 x 210 mm
(16.2 x 7.1 x 8.3 Inches)
- Weight: 3.2 kg (7 lbs)

Operating Temperature

- Ambient operating temperature: -20°C to +42°C (-4 F to +108 F)*
Maximum ambient operating temperature for housing mounted in direct sunlight:
+35°C (95 F)

Materials Specification

- Main body, bracket and sunshield: Aluminum
- Fastenings, wall fixings and locking clips: Stainless steel
- Window: Glass
- Camera mounting board: Bakelite
- Gaskets: Polyethylene and Neoprene
- Finish: Polyester powder coating RAL 9002 30% gloss white/grey

Approvals

- IP66
- CE: EN60950

*when used together with the AXIS 2120 and AXIS 2420



More information: www.axis.com